



Drying cabinet

TS560

Features

- Easy to read panel sign integrated in the door at a user-friendly height
- Handle along door – suitable for disabled people
- Option of activating child safety start lock
- Insulated door/quieter operation/more robust design
- 30 extensible hangers
- Magnetic edge on doors - eliminates risk of children being locked in
- Adjustable feet
- Two automatic drying programmes
- Door circuit breaker which interrupts the drying process when the door is opened
- Available with right or left hanging door

Options

- Shoe rack to make it easier to dry shoes and boots
- Glove hanger for more efficient drying of gloves, hats etc.



Main specifications		TS560
Drying capacity*	g/min	17
Unit power	kW	1.5
Energy consumption/kg washing	kWh	0.6
* 4 kg dry weight with 55% residual moisture after centrifugal drying for 2 hours on full power.		



Thinking of you
Electrolux

Electrical connection		TS560
Voltage		
230V 1AC 50-60 Hz	kW(A)	1.5(10)
Connections		
Outlet	ø mm	100
Evacuated air quantity	m³/h	50
Sound level		
Airborne sound level*	dB(A)	48
Weight		
	netto kg	56
Dimensions in mm		
A Width		600
B Depth		625
C Height		1915
D		255
E		60
F		300
G		100
H		1170
1 Operating panel		
2 Air outlet**		

Colour of front and side panels:
blue (NCS S2050-R90B), (RAL 250 6030)
light grey (NCS S3005-R80B), (RAL 260 7005)

* Acoustically tested with full load

** Connected with supplied drive interruption and hose



The drying cabinet in the picture is fitted with the accessories shoe rack and glove hanger to facilitate drying

