

ADVANCE LINE DISHWASHERS - BREAK TANK MODELS

FRONT LOADING DISHWASHERS - MODELS WITH BREAK TANK SYSTEM

Production: 540 dishes/h.
Capacity for dishes Ø 32 cm.
Basket size: 500 x 500 mm.
Wash cycles: 60", 90" and 180".
Rotating wash and rinse.
Tank with rounded corners.
Capacity: 25 litres.
Wash water heated by means of shielded elements on the tank : 2 KW.
Built-in rinse water boiler. Consumption: 2.7 litres/rinse.
Filters and trays in the wash tank.
Automatic wash and rinse dispenser.
Thermostatically adjusted: wash 60 °C, and rinse 90 °C.
Safety thermostat. Thermo stop system.
Digital display for rinsing and washing temperature.
Self diagnostic system.
Anti - return protection.
Safety switch for door opening.
Filters and trays in the wash tank

Equipment:
1 base basket CT-10 + 1 basket for dishes CP-16/18
+ 4 cutlery containers.

BRITISH PLUG

Electrical connection: 230 V - 1+N - 13 A.



Model	Version	Reference	Boiler Power	Electrical connection	Power KW	Dimensions mm
AD-45 BBT	MONO	1210305316	2 KW	230 V - 11.5 A	2.72	600x625x820
AD-45 BBT	DUAL	1210305316	4 KW	230 V - 20.6 A	4.72	600x625x820
AD-45 BBT	POWER	1210305316	6 KW	400 V - 11.5 A	6.72	600x625x820