

ELECTRIC PASS-THROUGH DISHWASHERS WITH BREAK TANK SYSTEM

Capacity for dishes Ø 42 cm.
 Wash cycles: 55", 75", 120", continuous washing position and stand-by position.
 The hood rises easily, with compensation system.
 Upper and lower rotating wash and rinse system.
 Heated by means of shielded elements.
 Tank with 4.5 kW heating element.
 Tank capacity: 45 litres.
 Filters and trays in the wash tank.
 Thermostatically adjusted:
 wash temperature 60 °C and rinse temperature 90 °C.
 Thermo stop system.
 Self diagnostic system.
 Anti - return protection.
 Safety thermostat.
 Digital display for rinsing and washing temperature.
 Automatic wash and rinse dispensers.
 Boiler with stainless steel heating elements for the water of the rinse.
 Water consumption: 3 litres by rinse.
 Safety switch for hood opening.



Model	Reference	Production Dishes/h	Technical features (*)	Equipment (**)	Power KW		Dimensions mm
					Boiler	Total	
AD-90 BBT	1210307416	900	M - 1 - C	S	6,00	11,10	675x675x1,400
AD-120 BBT	1210307272	1,200	T - 2 - H	Z	12,00	17,79	675x675x1,400

(*) TECHNICAL CHARACTERISTICS

M: Electrical connection: Single phase - 230 V - 1N - 29.7A Single phase.

T: Electrical connection: Tree phase - 400 V - 3N

1: One wash pump for lower and upper systems, 590 W.

2: Two independent wash pumps for lower and upper systems, 590 W each.

C: Boiler with 6 kW power.

H: Boiler with 12 kW power.

(**) EQUIPMENT

S: 1 basket CT-10 + 1 basket for dishes CP-16/18
+ 2 cutlery containers.

Z: 1 basket CT-10 + 2 basket for dishes CP-16/18
+ 8 cutlery containers.